

30 Series NMC 304 Battery

Energy & Power Optimized Battery Pack

SYSTEM FEATURES

- ✦ Power and Energy optimized
- ✦ Cycle Life Expectancy > 2500 Cycles
- ✦ Liquid Thermal Management
- ✦ Integrated BMS and CAN 2.0A Controlled
- ✦ Integrated Precharge and Isolation Measurement
- ✦ Parallel Topology for Multiple Packs in One Vehicle
- ✦ Development according to ECER100.2, ECER10 and UN38.3 - possible
- ✦ Development according to ISO26262 upto ASIL C - possible



e-mobitech.com

Altınay Elektromobilite ve Enerji Teknolojileri AŞ.
Şekerpınar Mh. Turgut Sk. No:9
Çayırova, Kocaeli / TÜRKİYE
+90 (262) 658 09 80
cell@e-mobitech.com

BATTERY PACK SPECIFICATIONS

ELECTRICAL DATA	VALUE	UNIT
Cell Type	NMC	
Energy (Installed / Usable)	35.5 / 32	kWh
Capacity	100	Ah
Nominal Voltage	355	V
Voltage - min. / max	269- 403	V
Charge Power Cont.	35	kW
Charge Power Peak @10s	42	kW
Discharge Power Cont.	35	kW
Discharge Power Peak @10s	105	kW
Cycle Life Expectancy @80DOD	> 2500	Cycles

MECHANICAL DATA		
Pressure drop @10l/min and 25°C	< 0.5	bar
Operating Temp. during discharging	-30 ~ 55	°C
Protection classes	IP67	
Weight	280 ± 10	kg
Dimensions	1310 x 650 x 285	mm

SYSTEM OPTION 1

Vehicle PDU

HV Distribution



SYSTEM OPTION 2

Battery System PDU

2-8 Parallel Battery Pack



DIMENSIONS

